

DATASHEET

VIS-NIR and UV-VIS-NIR fibered spectrometers



Our VIS-NIR and UV-VIS-NIR are ultra-broadband spectrometers designed for use with fibered probes over the complete UV, VIS & NIR spectral range, 350-2600nm or 200nm-2600nm. Those systems incorporate one Arcoptix FT-NIR Fourier-Transform scanning spectrometer for the NIR range 900-2600nm, and one multichannel grating spectrometer either for the VIS range (350-1000nm) or for the UV-VIS range (200-1025nm). The software supplied with the spectrometer automatically merges the spectra produced

■ Benefits

- Ultra-broad spectral ranges: 350-2600nm or 200-2600nm
- Very good resolution (<5 nm)
- Operation via optical fibers
- Fast measurements (down to 2 seconds)
- Very easy to use

■ Applications

- Transmission, diffuse reflectance
- Light source measurement (NIR Lasers, LED, Solar, ...)
- Material identification and quantification in various fields such as geology, food and beverage industry, medical diagnostics


DATASHEET

Specifications

Type	VIS-NIR-FIB	UV-VIS-NIR-FIB
Combined spectral range	350-2600nm	200-2600nm
VIS / UV-VIS spectrometer	Array detector grating spectrometer Spectral range: 350-1000nm Best efficiency (>30%): 350-850nm (see graph below)	Array detector grating spectrometer Spectral range: 200-1025nm Best efficiency(>30%): 200-450nm (see graph below)
NIR spectrometer	Fourier-Transform NIR spectrometer with extended-range InGaAs photodiode, 24-bit ADC, resolution 8cm ⁻¹ Spectral range: 900-2600nm Option: 2TE-cooled NIR detector (range 900-2500nm)	
Resolution	<5nm	
Fiber inputs	2x SMA-905 (one for VIS/UV-VIS, one for NIR)	
Min. measurement time	2 sec	
Software Interface	Windows 7 / 8 / 10	
Operating voltage (power)	12V DC (line power adaptor is included)	
Communication Interface	USB 2.0	
Product Dimensions	220mm x 180mm x 80mm	
Product Weight	2.5 Kg	
Operating Temperature	5°C – 35°C	

Efficiencies of VIS and UV-VIS spectrometer gratings

The VIS-NIR (350-2600nm) and the UV-VIS-NIR (200-2500nm) not only differ by their spectral ranges, but also by the efficiency of their grating in the VIS or UV-VIS spectral range. The VIS-NIR offers a better efficiency the range 350-1000nm, while the UV-VIS is rather optimized for the UV and has lower performance in the VIS range.



SPECIFICATIONS ARE SUBJECT TO CHANGES WITHOUT NOTICE.